

				CL09F.N50	CL12F.N50	CL18F.N60	CL24F.N30
Capaciteit	Koelen / Verwarmen	Nom	kW	2.6 / 2.9	3.5 / 3.9	5.3 / 5.8	7.0 / 7.7
Opgenomen vermogen ventilatormotor x aantal			W x No.	(19 x 1) + (5 x 1)	(19 x 1) + (5 x 1)	19 x 2	19 x 2
Stroom		Nom	A	0.80	0.80	0.80	1.00
Voeding			V, Ø, Hz	220-240, 1, 50	220-240, 1, 50	220-240, 1, 50	220-240, 1, 50
Luchtdebiet		H / M / L	m³/min	10.0 / 8.5 / 7.0	10.0 / 8.5 / 7.0	15.0 / 12.5 / 10.0	20.0 / 16.0 / 12.0
Geluidsdruk	Koelen	H / M / L	dB(A)	31 / 28 / 27	31 / 28 / 27	36 / 34 / 31	39 / 35 / 32
Geluidsvermogen	Koelen		dB(A)	55	55	54	58
Luchtontvochtigings-snelheid			l/h	0.55	1.11	1.58	2.65
Afmetingen		W x H x D	mm	900 x 190 x 460	900 x 190 x 460	1,100 x 190 x 460	1,100 x 190 x 700
Nettogewicht			kg	24.0	24.0	24.0	27.0
Leiding-aansluiting	Vloeistof		mm(inch)	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)
	Gas		mm(inch)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø12.7 (1/2)	Ø12.7 (1/2)
Externe druk	statische Min–Max		mmAq (Pa)	0~5 (0~50)	0~5 (0~50)	0~5 (0~50)	0~5 (0~50)