

Buitenunit model		HM093HFX UB60	HM123HFX UB60	HM143HFX UB60	HM163HFX UB60
Productgroep		350	350	350	350
Artikelnummer		463001	463002	463003	463004
Chassis code		UN60B	UN60B	UN60B	UN60B
Koelcapaciteit A35 / W18/7°C (Nom.)	kW	9,00/9,00	11,50/10,50	12,00/12,00	12,50/12,50
Verwarmingscapaciteit A7 / W35/55°C (Nom.)	kW	9,00/9,00	12,00/12,00	14,00/14,00	16,00/16,00
Verwarmingscapaciteit A-10/W35/55°C (Nom.)	kW	9,00/9,00	11,51/11,54	13,25/11,90	14,98/11,90
Geluidsvermogen (Low noise/Nominaal/Maximaal)	dB(A)	48/49/59	48/49/59	50/51/60	51/52/61
Geluidsrukniveau (@5 mtr)	dB(A)	27	27	29	29
Buitentemperatuurbereik koelen/verwarmen	°C	+10~-+46/-28~+35	+10~-+46/-28~+35	+10~-+46/-28~+35	+10~-+46/-28~+35
Luchthoeveelheid	M³/h	6.600	6.600	6.600	6.600
Afmetingen (BxDxH)	mm	1.560x625x1.180	1.560x625x1.180	1.560x625x1.180	1.560x625x1.180
Gewicht	kg	193,0	193,0	193,0	193,0
Koeltechnisch					
Koudemiddel/vulling	kg	R290/1,2	R290/1,2	R290/1,2	R290/1,2
t-CO ₂ equivalent/GWP		0,0036/3	0,0036/3	0,0036/3	0,0036/3
Elektrische gegevens					
Voeding	Ø/V/Hz	3/400/50	3/400/50	3/400/50	3/400/50
Voedingskabel	mm²	5x 2,5	5x 2,5	5x 2,5	5x 2,5
Opgenomen vermogen koelen (A30/W18/7°C)	kW	2,31/2,78	3,04/3,37	3,24/4,01	3,38/4,24
Opgenomen vermogen verwarmen (A7/W35/55°C)	kW	4,90/3,20	4,70/3,10	4,50/3,25	4,30/3,30
Werkvermogen	kW	4,00	4,00	4,66	5,33
Max. vermogen	kW	8,00	8,00	8,00	8,00
Afzekerwaarde warmtepomp	A	C16	C16	C16	C16
Afzekerwaarde in piekvermogen modus ⁽²⁾	A	C10	C10	C10	C10
Communicatiekabel binnenunit/buitenunit	Q x mm²	4x1,0	4x1,0	4x1,0	4x1,0
Waterzijdige gegevens					
Circulatiepomp		OH SUNG ODM 061P	OH SUNG ODM 061P	OH SUNG ODM 061P	OH SUNG ODM 061P
Waterhoeveelheid Nom.	l/min - M³/h	27/1,62	36/2,16	42/2,52	48/2,88