

INDOOR				PM05SP NSA	PM07SP NSA	PC09SQ NSJ	PC12SQ NSJ	PM15SP NSJ
Capacity	Cooling	Rated	W	1,500	2,100	2,500	3,500	4,200
	Heating	Rated	W	1,600	2,300	3,200	3,800	5,400
Sound Pressure	Cooling	S / L / M / H	dB(A)	19 / 27 / 30 / 35	19 / 27 / 31 / 36	19 / 27 / 32 / 36	19 / 29 / 34 / 38	19 / 29 / 35 / 40
	Heating	L / M / H	dB(A)	27 / 30 / 35	27 / 31 / 36	27 / 32 / 36	29 / 34 / 38	29 / 35 / 40
Sound Power	Cooling	Power	dB(A)	57	57	57	57	57
Air Flow Rate	Cooling	S / L / M / H	m³/min	3.5 / 5.0 / 5.8 / 7.1	3.5 / 5.0 / 6.1 / 7.4	3.5 / 5.0 / 6.4 / 7.7	3.5 / 5.3 / 6.7 / 8.1	3.5 / 5.4 / 7.0 / 8.7
		Max. (Power)	m³/min	10.1	10.1	10.1	10.1	10.1
	Heating	L / M / H	m³/min	5.0 / 5.8 / 7.1	5.0 / 6.1 / 7.4	5.0 / 6.4 / 7.7	5.3 / 6.7 / 8.1	5.4 / 7.0 / 8.7
Dehumidification Rate			l/h	0.9	0.9	1.1	1.2	1.2
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable			N x mm²	4C x 0.75	4C x 0.75	4C x 0.75	4C x 0.75	4C x 0.75
Dimension			mm	837 x 308 x 189	837 x 308 x 189	837 x 308 x 189	837 x 308 x 189	837 x 308 x 189
Net Weight			kg	8.7	8.7	8.7	8.7	8.7

INDOOR				PC18SQ NSK		PC24SQ NSK	
Capacity	Cooling	Rated	W	5,000		6,600	
	Heating	Rated	W	5,800		7,500	
Sound Pressure	Cooling	S / L / M / H	dB(A)	31 / 34 / 42 / 47		31 / 34 / 42 / 47	
	Heating	L / M / H	dB(A)	34 / 42 / 47		34 / 42 / 47	
Sound Power	Cooling	Power	dB(A)	59		65	
Air Flow Rate	Cooling	S / L / M / H	m³/min	8.0 / 10.5 / 13.1 / 15.5		8.0 / 10.5 / 13.1 / 16.1	
		Max. (Power)	m³/min	16.8		18.3	
	Heating	L / M / H	m³/min	10.5 / 13.1 / 15.5		10.5 / 13.1 / 16.1	
Dehumidification Rate			l/h	1.9		2.6	
Power Supply			Ø / V / Hz	1 / 220-240 / 50		1 / 220-240 / 50	
Power Supply Cable			N x mm²	4C x 0.75		4C x 0.75	
Dimension			mm	998 x 345 x 210		998 x 345 x 210	
Net Weight			kg	12.0		12.0	