

INDOOR				H09S1P.NS1
Capacity	Cooling	Rated	W	2,500
	Heating	Rated	W	3,200
Sound Pressure*	Cooling	S / L / M / H	dB(A)	19 / 27 / 31 / 35
	Heating	L / M / H	dB(A)	27 / 31 / 35
Sound Power	Cooling	Power	dB(A)	60
Air Flow Rate	Cooling	S / L / M / H	m³/min	2.0 / 5.7 / 6.9 / 8.1
		Max. (Power)	m³/min	11.2
	Heating	L / M / H	m³/min	5.7 / 6.9 / 8.1
Dehumidification Rate			l/h	1.1
Power Supply			Ø / V / Hz	1 / 220-240 / 50
Power Supply Cable			N x mm²	4C x 0.75
Dimension			mm	895 x 307 x 235
Net Weight			kg	12.5
ACCESSORIES & OTHERS				H09S1P.NS1
Wall Type Single Split Compatible				Y
Commercial Single Split Compatible				-
Dry Contact				Y
Wired Remote Controller				Y
ThinQ (Embedded Wi-Fi)				Y

INDOOR				H12S1P.NS1
Capacity	Cooling	Rated	W	3,500
	Heating	Rated	W	4,000
Sound Pressure*	Cooling	S / L / M / H	dB(A)	19 / 27 / 33 / 37
	Heating	L / M / H	dB(A)	27 / 33 / 37
Sound Power	Cooling	Power	dB(A)	60
Air Flow Rate	Cooling	S / L / M / H	m³/min	2.0 / 5.7 / 7.4 / 9.1
		Max. (Power)	m³/min	11.2
	Heating	L / M / H	m³/min	5.7 / 7.4 / 9.1
Dehumidification Rate			l/h	1.3
Power Supply			Ø / V / Hz	1 / 220-240 / 50
Power Supply Cable			N x mm²	4C x 0.75
Dimension			mm	895 x 307 x 235
Net Weight			kg	12.5
ACCESSORIES & OTHERS				H12S1P.NS1
Wall Type Single Split Compatible				Y
Commercial Single Split Compatible				-
Dry Contact				Y
Wired Remote Controller				Y
ThinQ (Embedded Wi-Fi)				Y