

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): TH-V16EM3-R							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	N		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Medium-temperature application						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	14	kW	Seasonal space heating energy efficiency	ηs	134	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C	Pdh	12.08	kW	Tj = - 7 °C	COPd	2.03	-
Degradation co-efficient (**)	Cdh	0.99	-				
Tj = 2 °C	Pdh	7.24	kW	Tj = 2 °C	COPd	3.16	-
Degradation co-efficient (**)	Cdh	0.99	-				
Tj = 7 °C	Pdh	5.08	kW	Tj = 7 °C	COPd	4.97	-
Degradation co-efficient (**)	Cdh	0.90	-				
Tj = 12 °C	Pdh	3.26	kW	Tj = 12 °C	COPd	6.52	-
Degradation co-efficient (**)	Cdh	0.95	-				
Tj = bivalent temperature	Pdh	12.08	kW	Tj = bivalent temperature	COPd	2.03	-
Tj = operation limit temperature	Pdh	11.61	kW	Tj = operation limit temperature	COPd	2.29	-
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	NA	kW	For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	NA	-
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Ppsych	NA	kW	Cycling interval efficiency	COPcyc	NA	-
				Heating water operating limit temperature	WTOL	80	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.025	kW	Rated heat output (*)	Psup	2.39	kW
Thermostat-off mode	P _{TO}	0.025	kW	Type of energy input	Electric		
Standby mode	P _{SB}	0.025	kW				
Crankcase heater mode	P _{CK}	0.000	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	9700	m ³ / h
Sound power level, outdoors	L _{WA}	57	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m ³ / h
Annual energy consumption	Q _{HE}	8227	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	η _{wh}	112	%
Daily electricity consumption	Q _{elec}	7.136	kWh	Daily fuel consumption	Q _{fuel}	NA	kWh
Annual electricity consumption	AEC	1570	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of the supplier: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): TH-V16EM3-R							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	N		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Medium-temperature application						
Parameters declared for	Colder climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	12	kW	Seasonal space heating energy efficiency	ηs	118	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = − 7 °C	Pdh	7.65	kW	Tj = − 7 °C	COPd	2.60	–
Degradation co-efficient (**)	Cdh	0.98	–				
Tj = 2 °C	Pdh	4.62	kW	Tj = 2 °C	COPd	3.60	–
Degradation co-efficient (**)	Cdh	0.94	–				
Tj = 7 °C	Pdh	2.90	kW	Tj = 7 °C	COPd	4.27	–
Degradation co-efficient (**)	Cdh	0.90	–				
Tj = 12°C	Pdh	3.34	kW	Tj = 12°C	COPd	6.75	–
Degradation co-efficient (**)	Cdh	0.95	–				
Tj = bivalent temperature	Pdh	9.53	kW	Tj = bivalent temperature	COPd	1.84	–
Tj = operation limit temperature	Pdh	6.86	kW	Tj = operation limit temperature	COPd	1.36	–
For air-to-water heat pumps: Tj = − 15°C (if TOL < − 20°C)	Pdh	9.53	kW	For air-to-water heat pumps: Tj = − 15°C (if TOL < − 20°C)	COPd	1.84	–
Bivalent temperature	Tbiv	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-22	°C
Cycling interval capacity for heating	Pcyc	NA	kW	Cycling interval efficiency	COPcyc	NA	–
				Heating water operating limit temperature	WTOL	80	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.025	kW	Rated heat output (*)	P _{sup}	5.14	kW
Thermostat-off mode	P _{TO}	0.025	kW	Type of energy input	Electric		
Standby mode	P _{SB}	0.025	kW				
Crankcase heater mode	P _{CK}	0.000	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	–	9700	m ³ /h
Sound power level, outdoors	L _{WA}	57	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	–	NA	m ³ /h
Annual energy consumption	Q _{HE}	9484	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	η _{wh}	88	%
Daily electricity consumption	Q _{elec}	8.993	kWh	Daily fuel consumption	Q _{fuel}	NA	kWh
Annual electricity consumption	AEC	1979	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of the supplier: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): TH-V16EM3-R							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	N		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Medium-temperature application						
Parameters declared for	Warmer climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	14	kW	Seasonal space heating energy efficiency	ηs	179	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = − 7 °C	Pdh	NA	kW	Tj = − 7 °C	COPd	NA	−
Degradation co-efficient (**)	Cdh	NA	−				
Tj = 2 °C	Pdh	13.35	kW	Tj = 2 °C	COPd	2.29	−
Degradation co-efficient (**)	Cdh	0.98	−				
Tj = 7 °C	Pdh	9.27	kW	Tj = 7 °C	COPd	4.07	−
Degradation co-efficient (**)	Cdh	0.97	−				
Tj = 12 °C	Pdh	3.74	kW	Tj = 12 °C	COPd	5.92	−
Degradation co-efficient (**)	Cdh	0.96	−				
Tj = bivalent temperature	Pdh	9.27	kW	Tj = bivalent temperature	COPd	4.07	−
Tj = operation limit temperature	Pdh	13.35	kW	Tj = operation limit temperature	COPd	2.29	−
For air-to-water heat pumps: Tj = − 15 °C (if TOL < − 20 °C)	Pdh	NA	kW	For air-to-water heat pumps: Tj = − 15 °C (if TOL < − 20 °C)	COPd	NA	−
Bivalent temperature	Tbiv	7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	Ppsych	NA	kW	Cycling interval efficiency	COPcyc	NA	−
				Heating water operating limit temperature	WTOL	80	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.025	kW	Rated heat output (*)	Psup	0.65	kW
Thermostat-off mode	P _{TO}	0.025	kW	Type of energy input	Electric		
Standby mode	P _{SB}	0.025	kW				
Crankcase heater mode	P _{CK}	0.000	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	−	9700	m ³ /h
Sound power level, outdoors	L _{WA}	57	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	−	NA	m ³ /h
Annual energy consumption	Q _{HE}	4219	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	η _{wh}	122	%
Daily electricity consumption	Q _{elec}	6.535	kWh	Daily fuel consumption	Q _{fuel}	NA	kWh
Annual electricity consumption	AEC	1438	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of the supplier: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): TH-V16EM3-R							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	N		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Low-temperature application						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	14	kW	Seasonal space heating energy efficiency	ηs	185	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = − 7 °C	Pdh	12.24	kW	Tj = − 7 °C	COPd	2.64	–
Degradation co-efficient (**)	Cdh	0.99	–				
Tj = 2 °C	Pdh	7.40	kW	Tj = 2 °C	COPd	4.33	–
Degradation co-efficient (**)	Cdh	0.99	–				
Tj = 7 °C	Pdh	5.20	kW	Tj = 7 °C	COPd	7.54	–
Degradation co-efficient (**)	Cdh	0.90	–				
Tj = 12°C	Pdh	3.54	kW	Tj = 12°C	COPd	9.24	–
Degradation co-efficient (**)	Cdh	0.93	–				
Tj = bivalent temperature	Pdh	12.24	kW	Tj = bivalent temperature	COPd	2.64	–
Tj = operation limit temperature	Pdh	11.27	kW	Tj = operation limit temperature	COPd	2.43	–
For air-to-water heat pumps: Tj = − 15°C (if TOL < − 20°C)	Pdh	NA	kW	For air-to-water heat pumps: Tj = − 15°C (if TOL < − 20°C)	COPd	NA	–
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcyc	NA	kW	Cycling interval efficiency	COPcyc	NA	–
				Heating water operating limit temperature	WTOL	80	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.025	kW	Rated heat output (*)	P _{sup}	2.73	kW
Thermostat-off mode	P _{TO}	0.025	kW	Type of energy input	Electric		
Standby mode	P _{SB}	0.025	kW				
Crankcase heater mode	P _{CK}	0.000	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	–	9700	m ³ /h
Sound power level, outdoors	L _{WA}	57	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	–	NA	m ³ /h
Annual energy consumption	Q _{HE}	6062	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	η _{wh}	112	%
Daily electricity consumption	Q _{elec}	7.136	kWh	Daily fuel consumption	Q _{fuel}	NA	kWh
Annual electricity consumption	AEC	1570	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of the supplier: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): TH-V16EM3-R							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	N		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Low-temperature application						
Parameters declared for	Colder climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	13	kW	Seasonal space heating energy efficiency	ηs	149	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = − 7 °C	Pdh	8.24	kW	Tj = − 7 °C	COPd	3.24	–
Degradation co-efficient (**)	Cdh	0.98	–				
Tj = 2 °C	Pdh	4.63	kW	Tj = 2 °C	COPd	4.37	–
Degradation co-efficient (**)	Cdh	0.94	–				
Tj = 7 °C	Pdh	3.00	kW	Tj = 7 °C	COPd	6.25	–
Degradation co-efficient (**)	Cdh	0.90	–				
Tj = 12°C	Pdh	3.51	kW	Tj = 12°C	COPd	8.30	–
Degradation co-efficient (**)	Cdh	0.94	–				
Tj = bivalent temperature	Pdh	10.93	kW	Tj = bivalent temperature	COPd	2.51	–
Tj = operation limit temperature	Pdh	7.39	kW	Tj = operation limit temperature	COPd	2.08	–
For air-to-water heat pumps: Tj = − 15°C (if TOL < − 20°C)	Pdh	10.93	kW	For air-to-water heat pumps: Tj = − 15°C (if TOL < − 20°C)	COPd	2.51	–
Bivalent temperature	Tbiv	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-22	°C
Cycling interval capacity for heating	Pcyc	NA	kW	Cycling interval efficiency	COPcyc	NA	–
				Heating water operating limit temperature	WTOL	80	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.025	kW	Rated heat output (*)	P _{sup}	5.61	kW
Thermostat-off mode	P _{TO}	0.025	kW	Type of energy input	Electric		
Standby mode	P _{SB}	0.025	kW				
Crankcase heater mode	P _{CK}	0.000	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	–	9700	m ³ /h
Sound power level, outdoors	L _{WA}	57	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	–	NA	m ³ /h
Annual energy consumption	Q _{HE}	8643	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	η _{wh}	88	%
Daily electricity consumption	Q _{elec}	8.993	kWh	Daily fuel consumption	Q _{fuel}	NA	kWh
Annual electricity consumption	AEC	1979	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of the supplier: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): TH-V16EM3-R							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	N		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Low-temperature application						
Parameters declared for	Warmer climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	14	kW	Seasonal space heating energy efficiency	η_s	262	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = − 7 °C	Pdh	NA	kW	Tj = − 7 °C	COPd	NA	–
Degradation co-efficient (**)	Cdh	NA	–				
Tj = 2 °C	Pdh	14.19	kW	Tj = 2 °C	COPd	3.12	–
Degradation co-efficient (**)	Cdh	0.98	–				
Tj = 7 °C	Pdh	9.04	kW	Tj = 7 °C	COPd	5.71	–
Degradation co-efficient (**)	Cdh	0.97	–				
Tj = 12°C	Pdh	3.80	kW	Tj = 12°C	COPd	8.68	–
Degradation co-efficient (**)	Cdh	0.94	–				
Tj = bivalent temperature	Pdh	14.19	kW	Tj = bivalent temperature	COPd	3.12	–
Tj = operation limit temperature	Pdh	14.19	kW	Tj = operation limit temperature	COPd	3.12	–
For air-to-water heat pumps: Tj = − 15°C (if TOL < − 20°C)	Pdh	NA	kW	For air-to-water heat pumps: Tj = − 15°C (if TOL < − 20°C)	COPd	NA	–
Bivalent temperature	Tbiv	2	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	Pcyc	NA	kW	Cycling interval efficiency	COPcyc	NA	–
				Heating water operating limit temperature	WTOL	80	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.025	kW	Rated heat output (*)	P _{sup}	0	kW
Thermostat-off mode	P _{TO}	0.025	kW	Type of energy input	Electric		
Standby mode	P _{SB}	0.025	kW				
Crankcase heater mode	P _{CK}	0.000	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	–	9700	m ³ /h
Sound power level, outdoors	L _{WA}	57	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	–	NA	m ³ /h
Annual energy consumption	Q _{HE}	2853	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	η_{wh}	122	%
Daily electricity consumption	Q _{elec}	6.535	kWh	Daily fuel consumption	Q _{fuel}	NA	kWh
Annual electricity consumption	AEC	1438	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of the supplier: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							



66329904999