

MU3R21

COOLING														
OPERATION	INDOOR UNIT OPERATING (CAPACITY INDEX, kBtu/h)					TOTAL CAPACITY						INPUT(W)		
						MIN.		RATED		MAX.				
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	TOTAL	Btu/h	kW	Btu/h	kW	Btu/h	kW	MIN.	RATED	MAX.
2 UNIT	5	5	-	-	10	7,200	2.11	10,000	2.93	12,000	3.52	313	524	744
	5	7	-	-	12	7,200	2.11	12,000	3.52	14,400	4.22	393	676	971
	5	9	-	-	14	8,400	2.46	14,000	4.10	16,800	4.92	478	846	1,224
	7	7	-	-	14	8,400	2.46	14,000	4.10	16,800	4.92	478	846	1,224
	7	9	-	-	16	9,600	2.81	16,000	4.69	19,200	5.63	571	1033	1,501
	5	12	-	-	17	10,200	2.99	17,000	4.98	20,400	5.98	620	1,132	1,653
	9	9	-	-	18	10,800	3.17	18,000	5.28	21,600	6.33	671	1,235	1,818
	7	12	-	-	19	11,400	3.34	19,000	5.57	22,800	6.68	724	1,342	2,087
	5	15	-	-	20	12,000	3.52	20,000	5.86	24,000	7.03	778	1,455	2,204
	9	12	-	-	21	12,600	3.69	21,000	6.15	24,150	7.08	835	1,574	2,406
	7	15	-	-	22	12,600	3.69	21,000	6.15	24,150	7.08	835	1,574	2,406
	5	18	-	-	23	12,600	3.69	21,000	6.15	24,150	7.08	835	1,574	2,406
	9	15	-	-	24	12,600	3.69	21,000	6.15	25,000	7.33	835	1,574	2,406
	12	12	-	-	24	12,600	3.69	21,000	6.15	25,000	7.33	835	1,574	2,406
	7	18	-	-	25	12,600	3.69	21,000	6.15	25,000	7.33	835	1,574	2,406
	9	18	-	-	27	12,600	3.69	21,000	6.15	25,000	7.33	835	1,574	2,406
	12	15	-	-	27	12,600	3.69	21,000	6.15	25,000	7.33	835	1,574	2,406
	12	18	-	-	30	12,600	3.69	21,000	6.15	25,000	7.33	835	1,574	2,406
15	15	-	-	30	12,600	3.69	21,000	6.15	25,000	7.33	835	1,574	2,406	
15	18	-	-	33	12,600	3.69	21,000	6.15	25,000	7.33	835	1,574	2,406	
3 UNIT	5	5	5	-	15	9,000	2.64	15,000	4.40	18,000	5.28	525	918	1,309
	5	5	7	-	17	10,200	2.99	17,000	4.98	20,400	5.98	619	1,097	1,565
	5	5	9	-	19	11,400	3.34	19,000	5.57	22,800	6.68	720	1,286	1,856
	5	7	7	-	19	11,400	3.34	19,000	5.57	22,800	6.68	720	1,286	1,856
	5	7	9	-	21	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	7	7	7	-	21	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	5	5	12	-	22	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	5	9	9	-	23	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	7	7	9	-	23	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	5	7	12	-	24	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	5	5	15	-	25	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	7	9	9	-	25	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	5	9	12	-	26	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	7	7	12	-	26	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	5	7	15	-	27	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	9	9	9	-	27	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	5	5	18	-	28	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	7	9	12	-	28	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	5	9	15	-	29	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	5	12	12	-	29	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	7	7	15	-	29	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	5	7	18	-	30	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	9	9	12	-	30	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	7	9	15	-	31	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	7	12	12	-	31	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	5	12	15	-	32	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	5	9	18	-	32	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	7	7	18	-	32	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	9	9	15	-	33	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856
	9	12	12	-	33	12,600	3.69	21,000	6.15	25,000	7.33	720	1,286	1,856

MU3R21

HEATING (NEW 21K)														
OPERATION	INDOOR UNIT OPERATING (CAPACITY INDEX, kBtu/h)					TOTAL CAPACITY						INPUT(W)		
						MIN.		RATED		MAX.				
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	TOTAL	Btu/h	kW	Btu/h	kW	Btu/h	kW	MIN.	RATED	MAX.
2 UNIT	5	5	-	-	10	7,200	2.11	12,000	3.52	13,800	4.04	333	638	770
	5	7	-	-	12	8,640	2.53	14,400	4.22	16,560	4.85	421	821	1,013
	5	9	-	-	14	10,080	2.95	16,800	4.92	19,320	5.66	516	1,024	1,286
	7	7	-	-	14	10,080	2.95	16,800	4.92	19,320	5.66	516	1,024	1,286
	7	9	-	-	16	11,520	3.38	19,200	5.63	22,080	6.47	621	1,237	1,585
	5	12	-	-	17	12,240	3.59	20,400	5.98	23,460	6.88	677	1,353	1,749
	9	9	-	-	18	12,960	3.80	21,600	6.33	24,840	7.28	734	1,470	1,930
	7	12	-	-	19	13,680	4.01	22,800	6.68	26,220	7.68	795	1,595	2,137
	5	15	-	-	20	14,400	4.22	24,000	7.03	26,600	7.80	858	1,730	2,200
	9	12	-	-	21	14,400	4.22	24,000	7.03	26,600	7.80	858	1,730	2,200
	7	15	-	-	22	14,400	4.22	24,000	7.03	26,600	7.80	858	1,730	2,200
	5	18	-	-	23	14,400	4.22	24,000	7.03	26,600	7.80	858	1,730	2,200
	9	15	-	-	24	14,400	4.22	24,000	7.03	26,600	7.80	858	1,730	2,200
	12	12	-	-	24	14,400	4.22	24,000	7.03	26,600	7.80	858	1,730	2,200
	7	18	-	-	25	14,400	4.22	24,000	7.03	26,600	7.80	858	1,730	2,200
	9	18	-	-	27	14,400	4.22	24,000	7.03	26,600	7.80	858	1,730	2,200
	12	15	-	-	27	14,400	4.22	24,000	7.03	26,600	7.80	858	1,730	2,200
	12	18	-	-	30	14,400	4.22	24,000	7.03	26,600	7.80	858	1,730	2,200
	15	15	-	-	30	14,400	4.22	24,000	7.03	26,600	7.80	858	1,730	2,200
	15	18	-	-	33	14,400	4.22	24,000	7.03	26,600	7.80	858	1,730	2,200
3 UNIT	5	5	5	-	15	10,800	3.17	18,000	5.28	20,700	6.07	546	997	1,370
	5	5	7	-	17	12,240	3.59	20,400	5.98	23,460	6.88	650	1,209	1,654
	5	5	9	-	19	13,680	4.01	22,800	6.68	26,220	7.68	762	1,436	2,010
	5	7	7	-	19	13,680	4.01	22,800	6.68	26,220	7.68	762	1,436	2,010
	5	7	9	-	21	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	7	7	7	-	21	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	5	5	12	-	22	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	5	9	9	-	23	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	7	7	9	-	23	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	5	7	12	-	24	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	5	5	15	-	25	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	7	9	9	-	25	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	5	9	12	-	26	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	7	7	12	-	26	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	5	7	15	-	27	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	9	9	9	-	27	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	5	5	18	-	28	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	7	9	12	-	28	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	5	9	15	-	29	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	5	12	12	-	29	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	7	7	15	-	29	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	5	7	18	-	30	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	9	9	12	-	30	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	7	9	15	-	31	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	7	12	12	-	31	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	5	12	15	-	32	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	5	9	18	-	32	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	7	7	18	-	32	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	9	9	15	-	33	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068
	9	12	12	-	33	14,400	4.22	24,000	7.03	26,600	7.80	821	1,560	2,068